Facility ID #:	Facility Name:	Location:	Permit #:	



Tank and Pipe Installation Supplement C

Your application is not complete until all requested information is submitted. Please complete every item on

this supplement to avoid o	delays in processing	your request.		
☐ Permit fees☐ Environmental Asse	ease submit: pplication for Undergro ssment Questionnaire n Design Report (if requ	(if required)	fajor Installation	
Check appropriate boxes f	or proposed installat	ion		
Tank #	THI	S LINE FOR	OFFICE USE	ONLY
Tank Capacity (gallons)				
Substance Stored				
Tank Configuration	☐ Underground ☐ Aboveground (with underground piping)	☐ Underground ☐ Aboveground (with underground piping)	☐ Underground ☐ Aboveground (with underground piping)	☐ Underground ☐ Aboveground (with underground piping)
Tank Usage	☐ Emergency Generator ☐ Heating Oil ☐ Gasoline Retail ☐ Other	☐ Emergency Generator ☐ Heating Oil ☐ Gasoline Retail ☐ Other	☐ Emergency Generator ☐ Heating Oil ☐ Gasoline Retail ☐ Other	☐ Emergency Generator ☐ Heating Oil ☐ Gasoline Retail ☐ Other
Tank Material	☐ StiP3 ☐ FRP ☐ Clad ☐ Other	☐ StiP3 ☐ FRP ☐ Clad ☐ Other	☐ StiP3 ☐ FRP ☐ Clad ☐ Other	☐ StiP3 ☐ FRP ☐ Clad ☐ Other
Tank Construction	☐ Double-walled ☐ Single-walled ☐ Multi-Compartment ☐ Other	☐ Double-walled ☐ Single-walled ☐ Multi-Compartment ☐ Other	☐ Double-walled ☐ Single-walled ☐ Multi-compartment ☐ Other	☐ Double-walled ☐ Single-walled ☐ Multi-compartment ☐ Other
Tank Manufacturer				
Tank Leak Detection	GW Monitoring Vapor Monitoring Interstitial ATG Other	GW Monitoring Vapor Monitoring Interstitial ATG Other	GW Monitorinjg Vapor Monitoring Interstitial ATG Other	GW Monitoring Vapor Monitoring Interstitial ATG Other
Tank Corrosion Protection	Galvanic Impressed Current Non-corrodible	Galvanic Impressed Current Non-corrodible	Galvanic Impressed Current Non-corrodible	Galvanic Impressed Current Non-corrodible
Spill Prevention	☐ Spill bucket ☐ Other	Spill bucket	Spill bucket	☐ Spill bucket ☐ Other
Overfill Prevention (indicate all)	☐ Ball Float ☐ Audible Alarm ☐ Positive Shutoff ☐ Other_	☐ Ball Float ☐ Audible Alarm ☐ Positive Shutoff ☐ Other	☐ Ball Float ☐ Audible Alarm ☐ Positive Shutoff ☐ Other	☐ Ball Float ☐ Audible Alarm ☐ Positive Shutoff ☐ Other
Product Pipe Material	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other
Product Pipe Construction	☐ Double-walled☐ Single-walled☐ Others	☐ Double-walled☐ Single-walled☐ Others	☐ Double-walled☐ Single-walled☐ Others	☐ Double-walled☐ Single-walled☐ Others

Pipe Manufacturer					
Type of Pipe	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	
Pipe Leak Detection	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	
Pipe Corrosion Protection	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	
Vent Pipe Material	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	
Other					
For connections to ex	cisting pipe, also descri pipe and method of co	be:			

	☐ Total length of each new product piping run	_			
	☐ Make and model of existing line leak detection equipment t	to be replaced			
	Describe the project—what are you planning to do? (attach addesign issues and any information not included above.	ditional sheets if n	ecessary). Inclu	ıde any s	pecial
Sita DI	an to include the following elements at a minimum:				
☐ F:	acility name		☐ North arrow	1	
	djacent water wells, public sewers, streams or bodies of water w imensioned or scaled distances between property lines, building			em(s)	
☐ T ☐ S ☐ A	ch existing UST system, locate the following elements by dime anks (AST and UST) Product pipe* Dispensers ump(s)* ny vapor or groundwater monitoring wells (including remediation ow only if any existing UST component requires disassembly or	s n wells)	place:		
For T	ch proposed UST system, locate the following elements by dim Fank(s), show: ank(s)	etection monitoring	·		
□ P □ A □ Li	Pipe(s), show: roduct Pipe(s) Il leak detection monitoring equipment** Il corrosion protection equipment associated with pipe(s)** ne leak detector if not installed in STP housing** ump(s)				
☐ F ☐ D ☐ If ☐ F ☐ If ins	ex connectors and method of corrosion protection** ispenser(s) connecting to existing pipe made by a different manufacturer, slor double-walled and/or suction pipe runs, show flow direction the talling a suction system, also include: Check valves** Solenoid valves** Product pipe ow relative location only (do not dimension or scale)	nrough the system	and the locatio	n of sump	os**
1. Is th 2. Is th 3. Is a	nmental Assessment: de depth to groundwater less than 50 feet below ground surface' de distance to surface water less than 100 feet from the project below domestic well located within 100 feet of the project boundary? The portion of a public sewage system located less than 100 feet	ooundary?	oundary?	Yes	No

If you answered yes to **any** of these questions, you must submit an Environmental Assessment Questionnaire with your permit application.